

# What is abstraction?

- Workable answer – a *blurring* of details
- Idea: agree to **ignore certain details** (*for now*)
  - e.g., with procedural abstraction – idea is to convert original problem to a series of simpler problems
- Works for data types too
  - Think (*and write code*) in terms of **abstract data types** like Lists, Stacks, Trees, ...
    - What should matter – what you can do with a List
    - What should not matter – what goes on inside the List
  - *Assume* the ADT works – just use it!

# A Priority Queue ADT

- ADT is defined by its **interface** – what it does
- If `PQItem` and `PriorityQueue` are defined types

```
void insert(PQItem, PriorityQueue *);  
    /* add the item to the queue */  
PQItem remove(PriorityQueue *);  
    /* always returns item with highest priority */  
int empty(PriorityQueue *);  
    /* true if queue has no items */  
void initialize(PriorityQueue *);  
    /* or similar constructor function */
```

- Never mind how it works – think about that later

# Interface is enough to use ADT

- Easy way to sort – let a priority queue do it

```
void easySort(PQItem a[], int n) {  
    int i; PriorityQueue pq;  
    initialize(&pq);  
    for (i=0; i<n; i++) /* put all items in priority queue*/  
        insert(a[i], &pq);  
    for (i=n-1; i>=0; i--) /* items come out sorted */  
        a[i] = remove(&pq);  
} /* There are more efficient ways to sort, but that's not the point. */
```

- The point is that we can use it without knowing how it works.
- **Abstraction is good!**

# Of course, it *does* have to work

- Many ways to implement – text covers 2:
  - Maintain a *sorted list* of items:
    - insert – some work: insure item is inserted in order
    - remove – easy: remove the first item
  - Keep items in an *unsorted array*:
    - insert – easy: append item as last array element
    - remove – harder: search for highest priority item, and move last array element to emptied slot
- Binary tree method works best – later topic

# Decomposition and C modules

- So user just needs the interface:
  - e.g., `#include "PriorityQueue.h"`
    - Which may vary between implementations – but better not to
- The implementation is in a separate file:
  - Usually `PriorityQueue.c`, and *separately compiled*
    - This file also has `#include PriorityQueue.h` in it
- This organization has at least two major benefits:
  - Implementation details hidden from user
    - User less likely to mess it up, & doesn't have to think about it
  - Critical interface declarations stored in a single place

# Scoping rules

- Refer to the “visibility” of identifiers

```
long x; float y; int z; /* “global” variables*/
void fn(char c, int x) { /* parameter x hides global x */
    double y = 3.14159; /* local y hides global y */
    extern int z; /* refer to global z */
    { char y; /* hides first local y */
      y = c; /* assign to second local y */
    }
    y = y / 3.0; /* assign to first local y */
    z++; /* increment global z */
}
```

- Translation unit – a file, and #included files
  - Extent of “global” scopes, unless extern is used

# Compiling, linking, & make files

- Compiling only – e.g., `gcc -c pgm.c`
  - Creates **object** file called `pgm.o` (or `pgm.obj` in DOS)
- Linking only – e.g., `gcc pgm.o -o pgm`
  - Makes **executable** file called `pgm` (or `pgm.exe` in DOS)
- Can automate process with a **Makefile**:

```
pgm: pgm.o                # dependency
    gcc pgm.o -o pgm      # action (tab is required)
pgm.o: pgm.c
    gcc -c pgm.c
```

- Then just type “**make**” – Unix tool executes the actions *as necessary* to satisfy the dependencies

# Dealing with multiple modules

- Imagine a program for factorial, consisting (for illustrative purposes only) of 3 modules:
  - factorial.h – contains the function prototype
  - factorial.c – implements the function
  - testfac.c – uses the function
- Both .c files `#include "factorial.h"`
- Makefile – separately compiles `testfac` and `factorial`, then links them
  - If just change `factorial.c` – `make` recompiles that file only and relinks to existing `testfac.o`

# Abstract lists

- Text's ch. 4 lists more abstract than ch. 2
  - Info stored as ItemType
    - Then `typedef int ItemType`, or any other type
      - `#include ItemInterface.h` – redefined as necessary
  - List node operations are very general:

```
void setLink(NodePointer, NodePointer)
NodePointer getLink(NodePointer)
void setItem(NodePointer, ListItem)
/* where typedef ItemType ListItem */
ListItem getItem(NodePointer)
```
- Idea is to hide the implementation details

# Even more abstract lists

- One way: store info as `void *`
  - Then can point to anything
  - Only way to apply `polymorphic` abstraction in C
- Another way: hide internal data structures completely – give no access to nodes
  - Not just function implementations can be hidden
  - Necessary to provide an `iterator` mechanism, because user has no direct access to links
    - Simplifies list usage, and prevents tampering

# Basic List ADT

- [basiclist.h](#) – (very) abstract data type for lists
  - Allows handling of any type of data:

```
typedef void *InfoPointer;
```
  - Completely hides implementation details:

```
typedef struct ListTag *ListPointer;
```

    - Structure declared here; defined in `basiclist.c`
    - Might be implemented as array or other way – user doesn't have to know; user can't mess it up
  - Requires initialization to set things up:

```
ListPointer createList(void);
```

    - In this case, have to allocate space for list structure, and initialize all pointers to NULL

# Basic list ADT (cont.)

- Accessor functions access info, not nodes

```
InfoPointer firstInfo(ListPointer);  
InfoPointer lastInfo(ListPointer);  
InfoPointer currentInfo(ListPointer);
```

- User cannot incorrectly handle nodes

- e.g., can never set `node->link = node;`

- Insert functions do not copy info, just pointers

```
void insertFirst(InfoPointer, ListPointer);
```

- Can also insert last, or before or after current

- Delete functions return copies of deleted pointers

```
InfoPointer deleteFirst(ListPointer);
```

- Can also delete last or **current**