

# A few more pointer points

- Beware null & wayward pointers! (Learn from [Binky](#))
- Command line arguments
  - `int main(int argc, char *argv[]) {...}`
  - Equivalent argv declaration: `char **argv`
  - Either way, `argv[i]` refers to  $i^{\text{th}}$  argument
- Pointers to functions – function name is a pointer
  - Can pass to another function as an argument
  - `void other ( int (*func)(func's parameters) )`
    - See `libqsort.c` in `~cs60/demo03` for example
- Complicated declarations – read from right to left
  - Decipher using K&R's `dc1.c` (in `~cs60/demo03`)

```
int printf(char *fmt, a1, a2, ...)
```

- Prints to `stdout` – formatted
  - Same as `fprintf(stdout, char *fmt, a1, ...)`
  - Variable length argument list after format – one for each `%` in format string (in order)
- `%[-][width][.][precision]character`
  - ‘-’ specifies left justification
  - width – maximum field width in characters
  - `[.][precision]` – for floating point nums only
  - Character – specific for type to convert
    - `d, i, o, x, u` – for integers
    - `f, e, g` – for floating point
    - `s` for strings, and `c` for chars

# Line input and output

- Note: K&R `getline` is non-standard – better to use `fgets` from `<stdio.h>`:

```
char *fgets(char *line, int max, FILE *fp);
```

- Reads at most `max - 1` characters, including `'\n'`
- The array, `line`, must be able to hold `max` chars

- But **do not use `gets(...)`** – it's **dangerous**

- `fputs` – alternative to `fprintf` to output lines:

```
int fputs(char *line, FILE *fp); /* returns EOF if error */
```

- Or just use `puts(...)` for `stdout`

```
int scanf(char *fmt, a1, a2, ...)
```

- Formatted input from `stdin`
- For all except `%c` – skips white space
- Arguments corresponding to conversion characters *must* be pointers:

```
int x;  
char word[20];  
scanf("%d %s", &x, word);
```

- Note – `word` is already a pointer, so no `&`
- Another note – `word` array must be large enough
- Also `sscanf` and `fscanf` – for input from a string or a file (i.e., like `sprintf` and `fprintf`)

# Variable-length argument lists

- `#include <stdarg.h>`
- `va_list ap;`
  - /\* first: declare pointer to unnamed args \*/
- `va_start(ap, last named-arg);`
  - /\* aim pointer at first unnamed argument  
(note: must be at least one named argument) \*/
- `type value = va_arg(ap, type)`
  - /\* get current unnamed argument, and increment \*/
- `va_end(ap);`
  - /\* must be called when done – before returning \*/

# File input/output

- `FILE *fp; /* declare a file pointer */`
- `fp = fopen("filename", mode);`
  - `/* associate a file with the pointer */`
    - mode is char \* – either "r", "w", or "a"
- Input or output using the file pointer:
  - `getc(fp); /* returns next int from file */`
  - `putc(intValue, fp); /* outputs value to file */`
  - `fscanf(fp, format, ...); /* input from file */`
  - `fprintf(fp, format, ...); /* output to file */`

# Error handling basics

- Do NOT print errors to `stdout`
  - Print error messages to `stderr` instead:  

```
fprintf(stderr, "message", args...);
```
- Often need to terminate execution due to errors
  - In main – 

```
return EXIT_FAILURE; /* or any non-zero */
```
  - In other functions – 

```
exit(EXIT_FAILURE);
```
- Sometimes want to check error status of file (`fp`)
  - General error – 

```
ferror(fp); /* returns 0 if no errors */
```
  - End-of-file – 

```
feof(fp); /* returns non-0 if end of file */
```

# C structures – some basics

- Structures are *user-defined types* with multiple data fields
- e.g., define structure to hold a char and a double:

```
struct example{ /* type is 2 words: struct example */
    char c;
    double d;
}; /* the semicolon is mandatory */
```

- Create a structure, and declare and assign a pointer

```
struct example e, *ep = &e;
```

- Or, if won't need to refer to type name again:

```
struct { /* can leave off the "tag" */
    char c;
    double d;
} e, *ep;
```



# More structure basics

- Access fields with the dot `'.'` operator
  - By using the structure's name: `e.d = 2.5;`
  - Or the pointer: `(*ep).c = 'a'; /* parens needed */`
- Easier to use the arrow `'->'` operator for pointers
  - `ep->c = 'a';`
- Can initialize all fields in one step:
  - `struct example e2 = { 'c', 97.14 };`
- Note – size of structure  $\geq$  sum of field sizes:
  - `sizeof e >= sizeof(char) + sizeof(double)`

# typedef

- Can precede any declaration with `typedef`

- Defines a name for the given type:

```
typedef struct example ExampleType;  
ExampleType e, *ep; /* e, ep same as prior slide */
```

- Can even use a defined type to define another:

```
typedef ExampleType *ETPointer;  
ETPointer ep; /* ep same as above */
```

- Note – can simplify code with macros too:

```
#define C(p) (p)->c  
C(ep) = 'b'; /* preprocessor substitutes correct code */
```

# Structures and functions

- Usually better to pass pointers – avoid copy costs
  - But gives function access to original fields
    - Note: `const` not guaranteed in C
- Do not return pointers to local structure variables
  - In this case, accept the copying costs
  - But okay if dynamically allocate memory for structure
- Returning defined types aids readability:
  - `ETPointer someFunction()` is easy to read
  - `struct example *someFunction()` is not

# Collections of structures

- Arrays – an alternative to “parallel arrays”
  - Mostly handle like all other array types
    - `ExampleType array[/*size*/], *p;`
    - `p = array + 2; /* p points at third struct */`
  - See keyword counting programs, K&R p. 134 & 137 (today’s demo programs in `~cs60/demo04/`)
- Linked data structures – a.k.a. self-referential

```
typedef struct node {
    DataType data;
    struct node *next; /* a pointer to next node */
} ListNode;
```

  - Also see binary search tree program, K&R pp. 140-2

# Unions

- Can hold different data types/sizes (at different times)
- e.g., define union to hold an `int` or a `double`:

```
union myValue{
    int x;
    double d;
} u, *up; /* u is a union, up can point to one */
```

- Access `x` or `d` by `u.` or `up->` just like structures
- `sizeof u` is size of largest field in union
  - Equals `sizeof(double)` in this case
- Often store inside a structure, with a key to identify type
  - Otherwise might be no way to know which field to access

# More library functions

- Become familiar with K&R appendix B!
- `<string.h>` – to deal with `char *` data
- `<ctype.h>` – to handle individual `chars`
- `<math.h>` – trig functions, logs, many more
  - Note: usually must link to `libm.a` – use `-lm`
- `<stdlib.h>` – various utilities
  - Inc. `atoi`, `qsort`, `rand`, `malloc`, `exit`, `system`, ...
- `<assert.h>` – one cool macro: `assert(int)`
- `<time.h>`, `<limits.h>`, ... – check them out!